

# HCS-8600POE Congress PoE Network Switcher



## Ordering Information

HCS-8600POE..... Congress PoE Network Switcher (supports PoE, KMX mode for HCS-8668/8638 series multimedia terminal, Normal mode for HCS-1082N series E-ink electronic nameplate) and both modes for HCS-8665 series multimedia terminal.

## Functions

- Based on TAIDEN originated GMC-STREAM Gigabit Multimedia Congress Stream technology
- Sync power on/off with the Congress Main Unit
- Built-in switch to choose work mode:
  - ◆ KMX mode: connecting DELEGATE ports to HCS-8668/8638 series congress terminals for power supply and transmission of conference data
  - ◆ Normal mode: connecting DELEGATE ports to HCS-8665 series congress terminals, HCS-1082N series E-ink electronic nameplates for power supply and conference data transmission
- Connecting DELEGATE ports to the Distributor HCS-8368T/50 to expand the number of units

## Interconnections

- ETHERNET port
  - ◆ KMX mode: Connection with CMU or EMU
  - ◆ Normal mode: Null
- DELEGATE standard ports for connection with HCS-8668/8638/8665 Series Multimedia Terminals, HCS-1082N series E-ink Electronic Nameplates (via Cat.5e/Cat.6 cable)
- 2 × 8P-DIN interface for connection with the Congress Main Unit or cascading to another HCS-8600POE (equipped with CBL8PPD-01 - 1-meter 8-pin extension cable with two plugs)

## Technical Specifications

### Electrical

Power supply.....AC 100 V - 240 V, 50 Hz / 60 Hz  
 Power output.....four power outputs, each output 48V DC, 3A  
 Power consumption.....400 W

### Mechanical

Mounting.....Tabletop or mounted in a 19" rack  
 Dimensions (h × w × d)  
 For table use, with feet.....48 × 480 × 288 mm  
 For 19" rack use.....45 × 480 × 288 mm  
 Weight.....3.6 kg  
 Color.....Black (PANTONE 419 C)