

Table 5.1.1 Quick lookup table of HCS-8600M CMU/EMU load capability (each outlet)

Type	Type No.	The extension cable length between the CMU(EMU) and the first Congress Unit connected to the socket			
		20 m	40 m	60 m	80 m
Equipped with 6.8" LCD, speaker and microphone	HCS-8685	9	8	7	7
Equipped with 4.3" LCD, speaker and microphone	HCS-4890N/80	9	9	9	8
	HCS-4890N/FM/80	9	9	9	8
Equipped with OLED, speaker and microphone	HCS-4838/80	11	11	10	10
	HCS-48U6/80	14	13	12	12
Equipped with 256*64 LCD, speaker and microphone	HCS-48U7/U8/U9/	13	12	12	11
Equipped with OLED, speaker and microphone	HCS-48U10/80	14	13	12	12
Equipped with 10" LCD, speaker and microphone	HCS-8635	7	7	6	6
Voting unit	HCS-4868/4869	52	50	48	46

***Note:**

- ☞ Cable Splitter HCS-4852T(N) is needed when the length of an extension cable exceeds 80 m. (Cable splitter is used as repeater only and cannot improve load capability.);
- ☞ For “Closed Loop - Daisy Chain” connection, load capability of each outlet is reduced by half.

Table 5.1.4 Quick lookup table of HCS-8600KMX load capability (each outlet)

Multimedia Terminal	The extension cable length between the HCS-8600KMX and the first Multimedia Terminal connected to the socket			
	20m	40m	60m	80m
HCS-8668/50	8	7	7	7
HCS-8638/50	8	7	7	7
HCS-8668/50+HCS-1082	6	6	6	6
HCS-8638/50+HCS-1082	7	6	6	6