

# HCL-404

## 4 Units Two-way Column Loudspeaker



### Overview

The two-way single-drive full-range column speaker comes with 4x4" midwoofers and 12x0.75" tweeters. Three tweeters form a linear tweeter sub-array in combination with a coaxial transducer and a midwoofer allowing smoother off-axis response. 15° fixed vertical coverage and accurate pointing reduce acoustic reflections and optimize speech intelligibility.

It can meet the needs of a conference sound reinforcement in small to medium-sized conference rooms. When combined with a woofer, the system gains a greater dynamic range and fulfills the sound reinforcement requirements for audio and video programs.


### Features

- 15° vertical direction
- Two-way column loudspeaker
- Composite carbon fiber units
- Can be combined with HCL-404J

### Applications



Small and Medium Meeting Rooms



Multifunction Halls



Hotels



Restaurants

### Specifications

Item	Parameter
Frequency Range	80Hz-20kHz (±3dB) / 60Hz-25kHz (-10dB)
Sensitivity	100dB
Nominal Impedance	8 Ohm
Rated Power	200W (AES)
Midwoofer Unit	4 × 4" complex carbon fiber diaphragm midwoofer units
Tweeter	12 × 0.75" nano carbon fiber diaphragm tweeters
Coverage Pattern - Nominal Coverage	100° (H) × 15° (V)
Max SPL	123dB SPL, 129dB SPL peak
Input Interface	2 × Phoenix 2pin
Enclosure Material	Birch + black polyurea finish
Dimensions (H × W × D)	450 × 130 × 180mm
Weight	5.2kg